



New Upgraded – Super impact & cut & vibration & contact heat protection. 15 gauge, high visibility yellow colour, new reinforcement.

KEY FEATURES

- Good quality TPR pads offer additional softness and great flexibility
- Thanks to thicker and special TPR design, it offers better impact protection
- The 15 gauge lining technology provides more comfort, flexibility and less hand fatigue comparing to normal 13 gauge one
- New reinforcement in the crotch offering better fit and comfort than others with cloth fabric
- Extra sponge pad inside the liner offering good vibration resistance
- High-Visibility yellow provides extra safety in challenging light conditions and perfect fit for high visibility work wear
- More soft and comfortable than other standard similar products in the market
- The velcro design makes it easy to wear and keep the glove in position when wearing




PRODUCT DETAILS

Liner	UHMWPE mixed with other yarns
Gauge	15
Coating	Nitrile
Finishing	Sandy
Colour	Yellow / Black
Size	8,9,10,11,12
Packing	6 pairs/polybag, 60 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

Works with impact hazard or cut hazard or vibration hazard or contact heat hazard or in challenging light conditions in dry or little oil or little wet conditions.

Such as oil & gas industry, construction industry, mining industry, automotive industry and etc.



CERTIFICATION

CE EN420:2003 + A1:2009

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):	4
Blade cut - coupe test (Index) (min.0 to Max. 5):	X
Tear (min.0 to max. 4):	4
Puncture (min.0 to max. 4):	3
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to Max. F, X - not tested):	C
Impact protection (P if pass, F if failed):	P

EN388:2016



4X43CP

**EN407:2004 Heat protection:
levels obtained in laboratory tests**

A - Burning behaviour:	X of 4
B - Contact heat:	1 of 4
C - Convective heat:	X of 4
D - Radiant heat:	X of 4
E - Small drops molten metal:	X of 4
F - Large quantity molten metal:	X of 4

EN407:2004



X1XXXX

X = not tested or testing method is unsuitable for the design of the gloves.

EN420:2003+A1:2009 Dexterity (min.0 to max.5):
level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent X-015 can normally be 3 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.

