



Highest level contact heat and convective heat protection, cut protection level C. Very flexible and comfortable. Both sides silicon coated.

KEY FEATURES

- Highest level for contact heat protection - level 4, it can withstand 500 °C
- Highest level for convective heat protection - level 4, it can withstand 500 °C
- Radiant heat protection up to 350 °C
- Cut level C protection
- One of the MOST flexible & comfortable heat resistant level 4 gloves in the market
- Both sides silicon coated providing great grip, extra heat resistance.
- Ambidextrous with both sides silicon coating design makes it can be used for up to twice longer time to save the cost



PRODUCT DETAILS

Liner	Thermo resistant yarns
Gauge	8
Coating	Silicon
Finishing	
Colour	Black / White & Yellow
Size	10
Packing	6 pairs/polybag, 72 pairs/carton

RECOMMENDED APPLICATIONS

Works with very high contact heat or very high convective heat or high radiant heat hazard or high cut hazard in DRY work conditions



CERTIFICATION

CE EN420:2003 + A1:2009

Category III

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4): **2**
Blade cut - coupe test (Index) (min.0 to Max. 5): **X**
Tear (min.0 to max. 4): **4**
Puncture (min.0 to max. 4): **X**
Cut resistance from sharp objects EN ISO
13997:1999 (min. 0 to Max. F, X - not tested): **C**
Impact protection (P if pass, F if failed): **-**

EN388:2016



2X4XC

**EN407:2004 Heat protection:
levels obtained in laboratory tests**

A - Burning behaviour: 4 of 4
B - Contact heat: 4 of 4
C - Convective heat: 4 of 4
D - Radiant heat: 3 of 4
E - Small drops molten metal: X of 4
F - Large quantity molten metal: X of 4

EN407:2004



4443XX

X = not tested or testing method is unsuitable for the design of the gloves.

EN420:2003+A1:2009 Dexterity (min.0 to max.5):
level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.

The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-401 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.

Please ensure the products are strictly used within their protection levels.

