

Extra softness. Super flexible, dexterity and comfort. OEKO-TEX Standard 100 certified. Sandy nitrile.

KEY FEATURES

- Great abrasion resistance with super flexibility, dexterity and comfort
- OEKO-TEX standard 100 certified for skin friendly
- Improved coating contributes to extra softness
- Great grip in oily and dry working condition
- 360° breathability to keep your hands cool full day



















PRODUCT DETAILS

Liner Gauge 15 Coating Nitrile

Nylon mixed with other yarns

Finishing

Sandy

Colour

Grey / Black

Size

6,7,8,9,10,11,12

Packing

12 pairs/polybag, 120 pairs/carton

Tariff number

61161020

RECOMMENDED APPLICATIONS

General purpose or precision works in dry or light oil conditions

Such asassembly and disassembly works, general handling, precision works, logistics, maintenance, inspection, sorting, machine operating, screwing, warehouse works...























Xcellent_® 3000

CERTIFICATION



EN420:2003 + A1:2009

Category II

EN388:2016 Mechnical protection: levels obtained in laboratory tests

Abrasion (min.0 to max. 4):

Blade cut - coupe test (Index) (min.0 to Max. 5):

Tear (min.0 to max. 4):

Puncture (min.0 to max. 4):

Cut resistance from sharp objects EN ISO 13997:1999 (min. 0 to Max. F, X - not tested):

Impact protection (P if pass, F if failed):

EN388:2016

1 4131A EN420:2003+A1:2009 Dexterity (min.0 to max.5): level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.

The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 3000 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNNING

Don't use in case of chemicals, moving machines or electrical risk.

Please ensure the products are strictly used within their protection levels.



