

Super abrasion resistance, great grip and additional durability. Touch screen function. 15 gauge, nitrile.

KEY FEATURES

- High quality nitrile dots contribute to super abrasion resistance, great grip and additional durability
- 10-finger touch screen functionality enables you to use all touch screen devices on the jobs
- Super flexible, soft and comfortable
- High visibility orange colour
- 360° breathability



Liner

Colour















PRODUCT DETAILS

Gauge 15

Coating Nitrile

Micro-foam & Dotted Finishing

Orange / Black & Orange

Nylon mixed with other yarns

Size 6,7,8,9,10,11,12

Packing 12 pairs/polybag, 120 pairs/carton

61161020 Tariff number

RECOMMENDED APPLICATIONS

General purpose work under dry, little wet/oily working conditions.

Such assembly and disassembly works, general handling, logistics, maintenance, inspection, sorting, machine operating, screwing, warehouse works...























Xcellent_® 3006

CERTIFICATION



EN420:2003 + A1:2009

Category II

EN388:2016 Mechnical protection: levels obtained in laboratory tests

Abrasion (min.0 to max. 4):

Blade cut - coupe test (Index) (min.0 to Max. 5):

Tear (min.0 to max. 4):

Puncture (min.0 to max. 4):

Cut resistance from sharp objects EN ISO 13997:1999 (min. 0 to Max. F, X - not tested):

Impact protection (P if pass, F if failed):

EN388:2016

4131A

1

EN420:2003+A1:2009 Dexterity (min.0 to max.5): **level 5.**

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.

The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 3006 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNNING

Don't use in case of chemicals, moving machines or electrical risk.

Please ensure the products are strictly used within their protection levels.



