



Superior cut protection sleeve - level F,
Very soft and comfortable. Velcro design.

KEY FEATURES

- Superior cut protection sleeve - the highest level at F
- Advanced yarns wrapping and knitting technology provides highest level cut protection but also great wearing comfort and softness
- The Velcro design holds the sleeve in position when wearing
- Straight cuff makes it good fit with glove
- 360° breathability




PRODUCT DETAILS

Liner	Steel fiber, UHMWPE, others
Gauge	13
Coating	N.A.
Finishing	N.A.
Colour	Blue
Length	45 cm
Packing	6 pairs/polybag, 120 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

General purpose, or works with high cut hazards.

Such as handling sharp edge parts, handling electronics parts, handling metal sheets or panels, cutting and etc.



CERTIFICATION

CE EN420:2003 + A1:2009

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):

3

Blade cut - coupe test (Index) (min.0 to Max. 5):

X

Tear (min.0 to max. 4):

4

Puncture (min.0 to max. 4):

X

Cut resistance from sharp objects EN ISO

13997:1999 (min. 0 to Max. F, X - not tested):

F

Impact protection (P if pass, F if failed):

-

EN388:2016



3X4XF

EN420:2003+A1:2009 Dexterity (min.0 to max.5):
level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.

The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 30-745 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.

Please ensure the products are strictly used within their protection levels.

